

BOSTON



CAPITAL
COLLECTION

house | office | public space

SPECIFICATION

Construction		Tufted loop pile
Gauge		1/10"
Dye method		SDN (Soution dyed)
Number of tufts	ISO 1763	± 141.700/ m2
Pile fibre		100% PA SDN
Pile weight	ISO 8543	710 gr/ m2 ± 5%
Pile height	ISO 1766	2-4 mm ± 5%
Tile backing		Polyflex
Total thickness	ISO 1765	6,5 mm ± 5%
Total weight	ISO 8543	4.800gr/m2 ± 7,5%
Tile size		50 x 50 cm

PERFORMANCE

Use clasification	method en 1307	33
Castor chair test	EN 985	A, continuous use
Thermal resistance	ISO 8302	0,08 m ² K/W
Dimensional stability	EN 986	pass
Luxury/ Comfort	EN 1307	classe 1
Static loading		anti-static
Impact sound insulation	ISO 140-8	ΔLw 24dB
Horizontal resistance	ISO CD 10965	3x10 ⁸ Ω
Vertical resistance	ISO CD 10965	4x10 ¹⁰ Ω
Reaction to fire	EN ISO 11925-2/ EN ISO 9239-1	Bfl -S1



Maintenance recommendations: Best results are achieved with dry cleaning

Recommended installation: Carpet tiles can be laid on a flat, dry, smooth surface (ČSN74 4505)

We recommend fixing the carpet squares over the entire surface with flexible glue. In case of laying without use adhesives, we recommend using double-sided adhesive tape. Directional arrows are printed on the back of each tile. Best results are achieved when installed in a checkerboard.